



ROHS-Compliant Product

Discrete Crystal Filters



Examples of our product range					
Type:	XF-14S01	XF-50S10	XF-107S251	XF-107S276	XF-120SXXX
Frequency (MHz)	1.401675	5.0	10.70	10.70	12.0
Passband (dB / kHz):	2.0 / ± 0.1375	3.0 / ± 0.18	3.0 / ± 50	6.0 / ± 110	1.0 / ± 25
Insertion loss max.(dB):	6.0	4.5	4.5	11.0	8.0
Ripple max.(dB):	2.0	2.5	2.0	2.0	1.0
Stopb. att. (dB /kHz): (dB / kHz):	60 / + 500 60/ - 100	40 / ± 0.35 60 / ± 0.6	60 / ± 300 80 / ± 500	60 / ± 380 -	35 / ± 100 -
Ultimate atten. (dB): (kHz ... kHz):	> 60	> 80	> 90	> 90 / ±1000...±10000	> 70 / ±250...±2000
Termination (Ω // pF):	50	50	50	50	50
Case style:	BF-104	BF-1	BF-32	BF-10	BF191-10.8
Temperature range (°C)	0 / +60	0 / +75	-20 / +70	0 / +60	-20 / +70
Max. input power	1.0 mW	1.0 mW	1.0 mW	1.0 mW	1.0 mW

Examples of our product range					
Type:	XF-214S06	XF-214S117	XF-214S119	XF-400S01	XF-700S44
Frequency (MHz)	21.4	21.4	21.4	40.0	70.0
Passband (dB / kHz):	6.0 / ± 1.3	3.0 >±100 ±20	3.0 > ± 50 ± 10	3.0 / ± 7.5	3.0 / ± 50
Insertion loss max.(dB):	3.5	10.0	9.0	6.0	4.0
Ripple max.(dB):	2.0	2.0	2.0	2.0	1.0
Stopb. att. (dB /kHz): (dB / kHz):	30 / ± 3.0 60 / ± 4.0	3:60 dB=1:3	60 / ± 1000 -	50 / ± 30 -	40 / ± 150 -
Ultimate atten. (dB): (kHz ... kHz):	> 90	> 70	> 90 / ±1500...±10k	> 60 / ±300...±2000	> 70 / ±400...±2000
Termination (Ω // pF):	350 // 30	50	50	50	50
Case style:	BF-1	BF-32	BF-32	BF-10	BF-6
Temperature range (°C)	-20 / +70	0 / +50	-20 / +70	-20 / +70	-10 / +50
Max. input power	1.0 mW	1.0 mW	1.0	1.0 mW	1.0 mW

KVG Quartz Crystal Technology GMBH

D-74922 Neckarbischofsheim P.O.B. 61 74924 Neckarbischofsheim Waibstadter Strasse 2 - 4
Tel: +49 (0) 7263 / 648 - 0 Fax: +49 (0) 7263 / 6196 e-mail:info@kvg-gmbh.de



ROHS-Compliant Product

Discrete Crystal Filters




Examples of our product range

Type:	XF-700S05	XF-710S03			
Frequency (MHz)	70.0	71.0			
Passband (dB / kHz):	3.0 / \pm 7.5	3.0 / \pm 90			
Insertion loss max.(dB):	6.0	6.0			
Ripple max.(dB):	1.0	1.0			
Stopb. att. (dB /kHz): (dB / kHz):	40 / \pm 30 -	60 / \pm 600 -			
Ultimate atten. (dB): (kHz ... kHz):	> 70 / \pm 100.. \pm 5k	> 80 / \pm 2k.. \pm 10k			
Termination (Ω // pF):	50	50			
Case style:	BF-32	BF-32			
Temperature range (°C)	-25 / +70	-20 / +70			
Max. input power	1.0mW	1.0mW			


KVG Quartz Crystal Technology GMBH

D-74922 Neckarbischofsheim P.O.B. 61 74924 Neckarbischofsheim Waibstadter Strasse 2 - 4
Tel: +49 (0) 7263 / 648 - 0 Fax: +49 (0) 7263 / 6196 e-mail:info@kvg-gmbh.de


Case Style



Case Style BF-32




Case Style BF-10





ROHS-Compliant Product

Discrete Crystal Filters



KVG Quartz Crystal Technology GMBH

D-74922 Neckarbischofsheim P.O.B. 61 74924 Neckarbischofsheim Waibstadter Strasse 2 - 4
Tel: +49 (0) 7263 / 648 - 0 Fax: +49 (0) 7263 / 6196 e-mail: info@kvg-gmbh.de